



RT12100A(12V10Ah)

Specification

Cells Per Unit	6
Voltage Per Unit	12
Nominal Capacity	10Ah@20hour-rate to 1.75V per cell @25°C
Weight	Approx. 2.90 Kg (Tolerance ± 5.0%)
Internal Resistance	Approx. 22 mΩ
Terminal	F1/F2
Max. Discharge Current	100A (5 sec)
Short Circuit Current	520A
Design Life	6~8 years (Float charging)
Max. Charging Current	3.0 A
Reference Capacity	C3 7.74AH C5 8.73AH C10 9.35AH C20 10.0AH
Standby Use Voltage	13.7 V~13.9 V @ 25°C Temperature Compensation: -3mV/°C/Cell
Cycle Use Voltage	14.6 V~14.8 V @ 25°C Temperature Compensation: -4mV/°C/Cell
Operating Temperature Range	Discharge: -20°C~60°C Charge: 0°C~50°C Storage: -20°C~60°C
Normal Operating Temperature Range	25°C ± 5°C
Self Discharge	RITAR Valve Regulated Lead Acid (VRLA) batteries can be stored for up to 6 months at 25°C and then recharging is recommended. Monthly Self-discharge ratio is less than 3% at 25°C. Please charge batteries before using.
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



RT series is a general purpose battery with 6~8 years design life in float service. It meets with IEC, JIS, BS, GB/T and YD/T standards. With advanced AGM valve regulated technology and high purity raw material, the RT series battery maintains high consistency for better performance and reliable standby service life. It is suitable for UPS/EPS, medical equipment, emergency light and security system applications.



ISO 9001



ISO 14001



OHSAS 18001




MH 28539



G4M20206-0910-E-16

Dimensions



Constant Current Discharge Characteristics : A (25°C)

F.V./Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	36.80	26.28	19.19	11.02	6.110	3.751	2.820	2.277	1.886	1.214	0.986	0.521
1.65V	34.22	24.83	18.35	10.58	5.900	3.632	2.733	2.215	1.837	1.200	0.974	0.512
1.70V	30.88	22.86	17.18	10.11	5.708	3.512	2.659	2.155	1.790	1.182	0.959	0.506
1.75V	27.67	20.93	15.99	9.667	5.500	3.389	2.579	2.100	1.745	1.166	0.947	0.500
1.80V	24.29	18.94	14.77	9.239	5.289	3.268	2.500	2.039	1.700	1.146	0.935	0.495
1.85V	19.28	15.48	12.25	7.958	4.744	2.994	2.311	1.896	1.585	1.076	0.880	0.470

Constant Power Discharge Characteristics : WPC (25°C)


F.V./Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	61.01	44.67	33.55	20.02	11.48	7.110	5.386	4.371	3.636	2.371	1.938	1.025
1.65V	57.39	43.02	32.55	19.42	11.15	6.916	5.242	4.268	3.555	2.349	1.917	1.010
1.70V	52.96	40.33	30.94	18.75	10.86	6.725	5.122	4.168	3.475	2.318	1.891	0.999
1.75V	48.50	37.59	29.21	18.10	10.52	6.521	4.990	4.077	3.399	2.291	1.868	0.988
1.80V	43.49	34.62	27.35	17.48	10.18	6.319	4.855	3.974	3.323	2.257	1.847	0.980
1.85V	35.25	28.79	23.02	15.20	9.185	5.821	4.508	3.708	3.109	2.124	1.741	0.932

(Note) The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values. The battery must be fully charged before the capacity test. The C₂₀ should reach 95% after the first cycle and 100% after the third cycle.

RT12100A(12V10Ah)



Discharge Characteristics Curve



Charge Characteristic Curve For Standby Use



Cycle Life In Relation To Depth Of Discharge



Relationship Between Charging Voltage And Temperature




Temperature Effects On Capacity



Storage Characteristics



Effect Of Temperature On Long Term Life



Life Characteristics Of Standby Use



(Note) All above information shall be changed without prior notice, Ritar reserves the right to explain and update the latest information.